



SECTION A-A

GENERAL TOLERANCE (HOUSING)

| | | | | | | | | | |
|-------|-------|-------|-------|--------|--------|--------|-------|-------|---------|
| 10MAX | 30MAX | 50MAX | 70MAX | 100MAX | 120MAX | 250MAX | 250VR | ANGLE | USED ON |
| ±0.15 | ±0.20 | ±0.30 | ±0.40 | ±0.50 | ±0.75 | ±0.9 | ±1.4 | ±30' | |

주 기

1. 지시하지 않는 R은 전부 0.3로 할것.
2. 제품기능상 유해한 BURR, 변형 및 WELDLINE 등이 없을것.
3. 적용 TERMINAL : ST730497,498
4. 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가 크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

1. UNLESS OTHERWISE SPECIFIED ALL R TO BE 0.3 RADIUS.
2. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
3. APPLICABLE TERM' : ST730497,498
- 4.6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE.

APPROVED

2018-12-10

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Te
rminal Co., LTD.

ISSUE MARK

| | | | | | | | | | |
|-----|-----------------|------|----------|------|------------|---------|--|-----------|-------------------|
| | | | | | MATERIAL | PBT | KOREA ELECTRIC TERMINAL CO., LTD. | | |
| | | | | | FINISH | NATURAL | | | |
| | | | | | WIRE RANGE | CLASS | | | |
| | | | | | INSULATION | TYPE | | | |
| LTR | REVISION RECORD | | DR. | CHK. | APP. | DATE | TOLERANCE EXCEPT AS NOTED ±0.2 | SCALE 2/1 | PART NO. MG611365 |
| | DR. | JANG | 97.11.19 | CHK. | KCC | 1/20 | PART NAME | | |
| | CHK. | JANG | 1/20 | APP. | Watanabe | 1/20 | SDL-6P PLUG. HOUSING | | |