



| GENERAL TOLERANCE (HOUSING) | | | | | USED ON |
|-----------------------------|-------|-------|-------|--------|---------|
| 10MAX | 20MAX | 45MAX | ANGLE | ECCENT | |
| ±0.2 | ±0.25 | ±0.3 | ±30' | 0.1 | |

NOTE

- 1.기능상 유해한 BURR 및 미성형 등이 없을 것.
- 2.적용 REC TERMINAL: ST730703.704 (7116-1300,1301).
- 15.MATERIAL: PBT - NATURAL COLOR.



| | | | | | | | | |
|-----|-----------------|------|----------|------|------------|-------------------------------|--------------------------------------|--|
| | | | | | MATERIAL | SEE NOTE | KOREA ELECTRIC TERMINAL CO., LTD. | |
| | | | | | FINISH | SEE NOTE | | |
| | | | | | WIRE RANGE | | CLASS 62C(.060) | |
| | | | | | INSULATION | | TYPE | |
| LTR | REVISION RECORD | DR | CHK | APP | DATE | THIS DRAWING EXPIRES ON | PART NO | |
| DR | MAN '97.12.03. | CHK | 97.12.03 | APP | 12/4 | SEE TABLE | SCALE 2/1 | |
| CHK | S.I.S.K.P | 12/4 | APP | 12/4 | | PART NAME | MG611530 | |
| | | | | | | | C 3P PLUG HS'G (DOOR S/W용) | |