



NOTE

1. APPLICABLE TERMINAL : ST740484-3, ST740484(Au)
ST740485-3, ST740485(Au)
2. APPLICABLE HOUSING : MG610396(7123-8345)
3. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

GENERAL TOLERANCE (HOUSING)					USED ON
10MAX	20MAX	45MAX	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	

주 기

1. 적용 TERMINAL : ST740484-3, ST740484(Au)
ST740485-3, ST740485(Au)
2. 적용 HOUSING : MG610396(7123-8345)
3. 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가 크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

SECTION A-A

SECTION B-B

APPROVED

2018-12-10

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Terminal Co., LTD.

ISSUE MARK

					MATERIAL	NYLON66	KET KOREA ELECTRIC ENGINEERED TERMINAL CO., LTD.	
					FINISH	NATURAL		
					WIRE RANGE		CLASS	
					INSULATION		TYPE	
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	PART NO.
	DR. MAN 95.05.27		CHK. Sik		95.05.27	SEE TABLE	2/1	MG620397
	CHK.		APP.	WATANABE		PART NAME	SDL 4M HOUSING ø 7.0 HOLE TYPE	