



GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

주 기

- 적용 HOUSING : MG610402(7123-8385)
- 적용 TERMINAL : ST740484-3, ST740484-G(AU)
ST740485-3, ST740485-G(AU)
- KET MARK : TAPER 15° (H : 0.3, SIZE; 1.5)
CAVITY NO. : TAPER 0° (H : 0.3, SIZE; 1.5)
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

- APPLICABLE HOUSING : MG610402(7123-8385)
- APPLICABLE TERMINAL : ST740484-3, ST740484-3(AU)
ST740485-3, ST740485-3(AU)
- KET MARK : TAPER 15° (H : 0.3, SIZE; 1.5)
CAVITY NO. : TAPER 0° (H : 0.3, SIZE; 1.5)
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

NO.	MATERIAL	COLOR
0	P B T	NATURAL
1		RED
2		BLUE
3		YELLOW
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8		LIGHT GREEN
9		MAGENTA
11	ORANGE	

APPROVED
2017-08-10
KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Terminal Co., LTD.

ISSUE MARK

					MATERIAL	SEE TABLE	KET KOREA ELECTRIC ENGINEERED TERMINAL CO., LTD.	
					FINISH	SEE TABLE		
△3	ECO-1606-055 근거 도면 변경	KJS	CKY	LSY	2016.06.03	WIRE RANGE	CLASS	YAZAKI
△2	ECO-1210-073 근거 도면 제작성	YM.K	CSH	HSY	2012.10.11	INSULATION	TYPE	7122-8386
△1	HINGE 강도보강	SJK	JYS	HSY	2011.11.10	TOLERANCE EXCEPT AS NOTED	SCALE	PART NO.
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	±0.20	1/1	MG620403
DR.	京 '91 12/02	CHK.				PART NAME		
CHK.	S. w k e r	APP.				SDL REC' HOUSING 8P		