



GENERAL TOLERANCE (HOUSING)

10MAX	30MAX	50MAX	70MAX	100MAX	120MAX	250MAX	250VR	ANGLE	ECCENT	USED ON
±0.15	±0.20	±0.30	±0.40	±0.50	±0.75	±0.90	±1.4	±30'	0.1	

NOTE

- UNLESS OTHERWISE SPECIFIED ALL RADII TO BE 0.3 RADIUS.
- MUST BE FREE OF BURR AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE HOUSING : SDL'SWP CONNERCOR
- KET MARK, CAVITY NO :INTAGLIO TAPER 15° (H:0.1-0.2, SIZE : 1.0)
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

주 기

- 지시하지 않은 R은 전부 0.3으로 한다.
- 기능상 유해한 BURR, 수축, 변형등이 없을 것.
- 적용 HOUSING : SDL'SWP CONNECTOR
- KET 문자, CAVITY NO : 양각 TYPE 구배 15° (문자 깊이 : 0.1-0.2, SIZE : 1.0 )
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs,PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NO.	MATERIAL	COLOR
* 0	NYLON	NATURAL
1		RED
2		BLUE
3		YELLOW
40		DARK GRAY
41		LIGHT GRAY
* 5		BLACK
6		DARK GREEN
		BROWN
		LIGHT GREEN
		MAGENTA
		ORANGE

**APPROVED**  
**2018-12-07**  
KOREA ELECTRIC  
TERMINAL CO., LTD.  
Korea Electric Te  
rminal Co., LTD.

ISSUE MARK

		MATERIAL		NYLON		KOREA ELECTRIC TERMINAL CO., LTD.	
		FINISH		SEE TABLE			
		WIRE RANGE				CLASS	
		INSULATION				TYPE	
△ ECO-1507-057 근거 도면 제작성 (색상 테이블 추가)		SY.L	CKY	LSY	'15.07.02		
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE
	JANG 98.01.08		CHK.KKJ		1/8 CJH 1/9	±0.2	2/1
CHK.	S.I.JANG 1/9		APP.	Watanabe 1/9		PART NO. MG631467	
						PART NAME	
						ø7 CLIP (SDL,SWP)	