



| GENERAL TOLERANCE (HOUSING) | | | | USED ON |
|-----------------------------|-------|-------|-------|---------|
| 10MAX | 20MAX | 45MAX | ANGLE | ECCENT |
| ±0.2 | ±0.25 | ±0.3 | ±30' | 0.1 |

NOTE

1. 기능상 유해한 BURR, 수축, 변형등이 없을 것.
 2. CLIP INSERTION FORCE : 8.0Kgf이하
- RETENTION FORCE : 10.0Kgf 이상

| NO. | METERIAL | COLOR |
|-----|----------|---------|
| 0 | | NATURAL |
| 1 | NYLON66: | RED |
| 2 | | BLUE |
| 3 | | YELLOW |
| 4 | | GRAY |
| 5 | | BLACK |
| 6 | | W/GREEN |
| 7 | | BROWN |
| 8 | | GREEN |



ISSUE MARK

| | | | | | | | | |
|-----|-----------------|------|-----|------|------------|------------------------|-----------------------------------|---------------------------|
| | | | | | MATERIAL | SEE TABLE | KOREA ELECTRIC TERMINAL CO., LTD. | |
| | | | | | FINISH | SEE TABLE | | |
| | | | | | WIRE RANGE | CLASS | | 1.7 - 2.6t |
| | | | | | INSULATION | TYPE | | |
| LTR | REVISION RECORD | DR | CHK | APP. | DATE | THROUGH REPORT OR NOTE | PART NO. | MG631929 |
| DR | WON. 2000.11.28 | CHK | 97 | | 11/29 | SEE TABLE | PART NAME | .090 II Ø7 CLIP(KEY HOLE) |
| CHK | | APP. | CHW | | 11/29 | | | |