



GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

**주 기**

- 1.지시하지 않은 반경 R은 0.3로 한다
- 2.기능상 유해한 BURR 및 WELDLINE등이 없을것.
3. 적용 HS'G :  
030(91A), 060(62C), 110(58T),040 WP(91RK) CONN'T
- 4.제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가 크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

**NOTE**

1. UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3RADIUS.
2. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
3. APPLICABLE HOUSING :  
090(91A), 060(62C), 110(58T), 040WP(91RK) CONN'T
- 4.6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE.

NO.	MATERIAL	COLOR
0	NYLON66:	NATURAL
1		RED
2		BLUE
3		YELLOW
4		GRAY
5		BLACK
6		W/GREEN
7		BROWN
8	GREEN	

\*

**APPROVED**  
**2018-12-07**  
KOREA ELECTRIC  
TERMINAL CO., LTD.  
Korea Electric Te  
rminal Co., LTD.

ISSUE MARK

					MATERIAL	SEE TABLE	<b>KET</b> KOREA ELECTRIC ENGINEERED TERMINAL CO., LTD.	
					FINISH	SEE TABLE		
					WIRE RANGE	CLASS	0.7 - 1.6t	
					INSULATION	TYPE		
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	PART NO.
	DR. KYM 02.04.09					SEE TABLE	2/1	MG632579
	CHK.					PART NAME	A CLIP (ø 7 KEY HOLE)	
	APP.							