



KEY HOLE PANEL



KEY HOLE PANEL DIMENSIONS



GENERAL TOLERANCE (HOUSING)

10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1

USED ON


## NOTE

- UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.3 RADIUS.
- MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE HOUSING : 090II FEMALE HOUSING

## 주 기

- 지시하지 않은 R은 0.3으로 할 것.
- 가능성 유해한 BURR, 수축, 변형등이 없을 것.
- 작용 HOUSING : 090II FEMALE HOUSING

NO.	MATERIAL	COLOR
0		NATURAL
1		RED
2	NYLON66	BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
*		BLACK
5		DARK GREEN
6		BROWN
7		LIGHT GREEN
8		MAGENTA
9		ORANGE
11		



ISSUE MARK

MATERIAL		SEE TABLE		KOREA ELECTRIC TERMINAL CO., LTD.	
FINISH		SEE TABLE		CLASS 090 II	
WIRE RANGE			TYPE		
INSULATION			SCALE 2/1		PART NO MG632970
REVISION RECORD		DR	CHK	APP	DATE
MKN0 2003.12.09					05.04.04
CHK					12/09
PART NAME		φ7 KEY HOLE CLIP (NEW TYPE)			