



GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

NO.	MATERIAL	COLOR
0	NYLON66	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
* 5		BLACK
6		DARK GREEN
7		BROWN
8		LIGHT GREEN
9	MAGENTA	
11	ORANGE	

주 기

1. 기능상 유해한 BURR, 수축, 변형등이 없을 것.
2. CLIP 삽입력 : 12Kgf 이하, 이탈력 : 15Kgf 이상
3. 적용 HOUSING : 090II HOUSING

NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. CLIP INSERTION FORCE : 12Kgf ↓
RETENTION FORCE : 15Kgf ↑
3. APPLICABLE HOUSING : 090II HOUSING



ISSUE MARK

					MATERIAL	SEE TABLE	KET KOREA ELECTRIC ENGINEERED TERMINAL CO., LTD.	
					FINISH	SEE TABLE		
					WIRE RANGE	CLASS	0.7 - 1.6t	
					INSULATION	TYPE		
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	PART NO.
						SEE TABLE	2/1	MG633870
DR.	KBS 2007.06.15	CHK.	---	---	6/18	PART NAME	090 II φ7 CLIP (KEY HOLE REVERSE)	
CHK.		APP.	---	---	6/18			