



NO.	MATERIAL	COLOR
* 0	NYLON	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8	LIGHT GREEN	
9	MAGENTA	
11	ORANGE	

GENERAL TOLERANCE (HOUSING)									USED ON
10MAX	30MAX	50MAX	70MAX	100MAX	120MAX	250MAX	250VR	ANGLE	
±0.15	±0.20	±0.30	±0.40	±0.50	±0.75	±0.90	±1.40	±30'	

주 기

- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
- CLIP HOUSING 삽입력 : 6 kgf 이하
이탈력 : 11 kgf 이상
- 적용 HOUSING : 090II SERIES
- KET 문자 : 기울기 15°(H; 0.1 0.2, SIZE; 1.5)
PART & CAVITY NO.: 기울기 0°(H; 0.1 0.2, SIZE; 1.5)
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- CLIP HOUSING INSERTION FORCE : 6 kgf MAX
RETENTION FORCE : 11 kgf MIN
- APPLICABLE HOUSING : 090II SERIES
- KET MARK : TAPER 15° (H; 0.1~0.2, SIZE; 1.5)
PART & CAVITY NO. : TAPER 0°(H; 0.1~0.2, SIZE; 1.5)
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE

APPROVED
2019-11-06
KOREA ELECTRIC
TERMINAL CO., LTD.
Connector Development Team 1

ISSUE MARK

					MATERIAL	SEE TABLE	KET KOREA ELECTRIC ENGINEERED TERMINAL CO., LTD.	
					FINISH	SEE TABLE		
					WIRE RANGE	CLASS	1.3 - 2.6 t	
					INSULATION	TYPE	090II CLIP	
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	PART NO.
						SEE TABLE	2/1	MG635710
DR.	KJH 2014.05.19	CHK.				PART NAME	090II Ø 7 CLIP (KEY HOLE)	
CHK.	HYJ 2014.05.20	APP.	HJB	2014.05.20				