



GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

주 기

1. 기능상 유해한 BURR 및 미성형이 없을것.
2. 상대 HOUSING PART NO. : MG653026
3. 적용 TERM' : ST740771 / ST740959

NOTE

1. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE HOUSING : MG653026
3. APPLICABLE TERMINAL : ST740771 / ST740959



ISSUE MARK

NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG673024	040III 20P MALE HS'G	PBT	NATURAL
②	MG673025	040III 20P MALE R/HOLDER	PBT	NATURAL

MATERIAL	SEE TABLE		KET KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE		
WIRE RANGE		CLASS	040III
INSULATION		TYPE	
LTR	REVISION RECORD	DR	PART NO.
DR	KYM 2004.01.30	CHK	MG643023
CHK	01.30	APP	
SCALE 2/1		PART NAME	
		040III 20P MALE ASS'Y	