



GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

주 기

1. 기능상 유해한 BURR 및 미성형이 없을것.
2. 상대 HOUSING PART NO. : Y7283-5973-40
3. 적용 'TERM' : ST740771 / ST740959

NOTE

1. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE HOUSING : Y7283-5973-40
3. APPLICABLE TERMINAL : ST740771 / ST740959



SECTION A-A



NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG673249	O40II 2P MALE HS'G	PBT	L/GRAY
②	MG673250	O40II 2P MALE R/HOLDER	PBT	L/GRAY

MATERIAL		SEE TABLE	KOREA ELECTRIC	
FINISH		SEE TABLE	TERMINAL CO., LTD.	
WIRE RANGE			CLASS	.040
INSULATION			TYPE	7282-5973-40
LTR	REVISION RECORD	DR	CHK	APP.
DR	HEO S.H. 04.8.23	CHK		
CHK	8/23	APP.	8/23	
SCALE		2/1	PART NO.	
PART NAME		O40 III 2P MALE ASS'Y (TKN02MGY)		