





SECTION A-A



TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

주 기

- 기능상 유해한 BURR 및 미성형이 없을것.
- 상대 HOUSING PART NO. : MG652630
- 적용 TERMINAL NO. : ST740928 / ST740929

NOTE

- MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE HOUSING NO. : MG652630
- APPLICABLE TERMINAL NO. : ST740928/ ST740929

NO.	PART NO.	PART NAME	MATERIAL	FINISH
1	MG673270	030 2M HOUSING(A02MW)	PBT	NATURAL
2	MG673271	030 2M HOUSING R/H	NYLON66	YELLOW



ISSUE MARK

				MATERIAL SEE TABLE		KOREA ELECTRIC TERMINAL CO., LTD.	
				FINISH SEE TABLE			
				WIRE RANGE		CLASS 91AC.030)	
				INSULATION		TYPE 7282-8629	
LTR	REVISION RECORD	DR	CHK	APP	DATE	TOLERANCE DEPOT AS PER	
						SCALE 2/1	
DR	HEO S.H 04.8.23	CHK.				PART NO. MG643269	
CHK.	---	8/23	APP.	---	8/23	PART NAME	
						030 2M HOUSING ASSY (A02MW)	