




SECTION A--A



GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

주 기

1. 기능상 유해한 BURR 및 미성형이 없을것.
2. 상대 HOUSING PART NO. : MG651444
3. 적용 TERMINAL NO. : ST740928 / ST740929

NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE HOUSING NO. : MG651444
3. APPLICABLE TERMINAL NO. : ST740928/ ST740929

NO.	PART NO.	PART NAME	MATERIAL	FINISH
1	MG673273	030 3M HOUSING(A03MW)	PBT	NATURAL
2	MG673274	030 3M R/H(A03MW)	NYLON66	NATURAL

2006.01.04

ISSUE MARK

					MATERIAL	SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.	
					FINISH	SEE TABLE		
					WIRE RANGE			
					INSULATION			
							CLASS	91A(.030)
							TYPE	7282-8630
LTR	REVISION RECORD	DR	CHK	APP.	DATE	TOLERANCE REF. IN NOTES	PART NO.	MG643272
DR.	HEO S.H 04.8.23	CHK				SCALE		
CHK.	8/23	APP.			8/23	2/1		
						PART NAME		030 3M HOUSING ASSY (A03MW)