



GENERAL TOLERANCE (HOUSING)

10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	USED ON
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

NOTE

- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL : ST731273/1274/1275(0.80T)
ST731338/1339/1340(0.64T)
WIRE SEAL : MG683894/3895/3896/3897
DUMMY SEAL : MG683898
MALE ASSY : MG655447
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

NO.	MATERIAL	COLOR
0	P B T	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8		LIGHT GREEN
9		MAGENTA
11		ORANGE

주 기

- 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
- 적용 TERMINAL : ST731273/1274/1275(0.80T)
ST731338/1339/1340(0.64T)
WIRE SEAL : MG683894/3895/3896/3897
DUMMY SEAL : MG683898
MALE ASSY : MG655447
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안 된다.

APPROVED

2016-02-25

**KOREA ELECTRIC
TERMINAL CO., LTD.
Connector Development
Team 1**

ISSUE MARK

NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG675451	060 WP 8F HOUSING	SEE TABLE	SEE TABLE
②	MG675452	060 WP 8F F/HOLDER	PBT	NATURAL
③	R602368	060 WP 8P INNER SEAL	SILICONE	RED

MATERIAL	SEE TABLE		KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE		
WIRE RANGE		CLASS	060
INSULATION		TYPE	WP
TOLERANCE EXCEPT AS NOTED	SEE TABLE	SCALE	1/1
PART NAME	060 WP 8F ASSY		
REVISION RECORD	DR. JSY 2011.09.09	CHK. CWK 09/09	
	CHK. CWK 09/09	APP. KKJ 09/09	