CUSTOMER DRAWING

PART NO. MG645750

NO.	PART NAME	PART NO.	MATERIAL	COLOR
1	250 6M HOUSING	MG675872	SEE TABLE	SEE TABLE
2	250 6M SPACER	MG675873-41	PBT	L/GRAY

GENERAL TOLERANCE (HOUSING)										USED ON
10MAX	30MAX	50MAX	70MAX	100MAX	125MAX	250MAX	250VR	ANGLE	ECCENT	
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30°	0.1	





SECTION A-A



NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL (250) : ST741206,741207,741208
   APPLICABLE CLIP : MG631471,2019,1267,1929,1268,3815,3862 3870,2970
3. MATCHING HOUSING : MG655697
4. THE MOLD DRAWING IN THE SAME WAY. SPACER IS NORMAL CONDITION MAINTENANCE AND SUPPLY WITH FIRST LOCKING.
5. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD,MERCURY, CADMIUM,HEXAVALENT CHROMIUM,PBBs,PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.







주 기

1. 기능상 유해한 BURR 및 WELDLINE등이 없을것.
2. 적용 TERMINAL (250) : ST741206,741207,741208
   적용 CLIP :MG631471,2019,1267,1929,1268,3815,3862, 3870,2970
3. 상대 HOUSING : MG655697
4. SPACER는 본 도면과 같이 1차 LOCK'G 상태로 유지, 공급할것.
5. 제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs,PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.



NO.	MATERIAL	COLOR
* 0	PBT	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8		LIGHT GREEN
9		MAGENTA
11		ORANGE

APPROVED
2018.12.07
KOREA ELECTRIC TERMINAL CO., LTD.
Product Development Team 1

ISSUE MARK

LTR	REVISION RECORD	DR.	CHK.	APP.	DATE

DR. HSR '13.12.31	CHK. CKY '13.12.31		
CHK. WSW '13.12.31	APP. CWK '13.12.31		

MATERIAL	SEE TABLE	KET ENGINEERED	KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE		
WIRE RANGE		CLASS	
INSULATION		TYPE	250
TOLERANCE SHEET AS SHOWN	SEE TABLE	SCALE 1/1	PART NO. MG645750
PART NAME	250 6M ASSY		