




SECTION A-A




GENERAL TOLERANCE (TERMINAL)					GENERAL TOLERANCE (HOUSING)					USED ON		
10MAX	20MAX	45MAX	ANGLE	ECCENT	10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.25	±0.3	±30'	0.1	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

NO.	MATERIAL	COLOR
0	PBT-GF30	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8		LIGHT GREEN
9		MAGENTA
11		ORANGE



P.C.B. LAYOUT

(GENERAL TOLERANCE : ±0.1)



주 기

1. 기능상 유해한 BURR 및 변형이 없을것.
2. 적용 FEMALE HOUSING : MG655758
3. 제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs,PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

1. MUST BE FREE OF BURR AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICATION FEMALE HOUSING : MG655758
3. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

APPROVED

2018-12-07

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Terminal Co., Ltd.

ISSUE MARK

NO.	PART NAME	PART NO.	MATERIAL	FINISH	QTY.
①	025 24M PCB HOUSING (H2T)	MG676064	SEE TABLE	SEE TABLE	1
②	025 PCB MALE TM'L-2.54 PITCH (L)	ST792554-2	BRASS	Sn 후도금 (Reflow)	12
③	025 PCB MALE TM'L-2.54 PITCH (S)	ST792555-2	BRASS	Sn 후도금 (Reflow)	12

MATERIAL	SEE TABLE	KET KOREA ELECTRIC TERMINAL CO., LTD.	
FINISH	SEE TABLE		
WIRE RANGE		CLASS	
INSULATION		TYPE	
DR.	LJY '14.10.29	SCALE	2/1
CHK.	CHK YSW '14.10.29	PART NO.	MG645878
APP.	APP. BIN '14.10.29	PART NAME	025 24M PCB ASSY(H2T)