

CUSTOMER DRAWING REF. NO. MG6458B3

GENERAL TOLERANCE (TERMINAL)				GENERAL TOLERANCE (HOUSING)				USED ON	
10MAX	20MAX	45MAX	ANGLE	10MAX	50MAX	100MAX	250VVR	ANGLE	ECCENT
±0.2	±0.25	±0.3	±30'	±0.2	±0.3	±0.55	±1.4	±30'	0.1

NO.	MATERIAL	COLOR
0	PPS-GF40	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8		LIGHT GREEN
9		MAGENTA
11		ORANGE

SECTION A-A

SECTION B-B

DETAIL C (S= 5/1)

P.C.B. LAYOUT (GENERAL TOLERANCE : ±0.1)

주 기
 1. 기능상 유해한 BURR 및 변형이 없도록
 2. 적용 FEMALE HOUSING : MG655827
 3. TIN-PLATED TERMINAL - TYPE A Sn(MATTE), (MS915-01)
 Ni-PLATED UNDER + Sn(유광) + Reflow
 4. 재봉내 함유된 6대 유해물질 (납,수은,카드뮴,스기크롬, PBBS,PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE
 1. MUST BE FREE OF BURR AND IMPERFECTION THAT AFFECT FUNCTION.
 2. APPLICATION FEMALE HOUSING : MG655827
 3. TIN-PLATED TERMINAL - TYPE A Sn(MATTE), (MS915-01)
 Ni-PLATED UNDER + Sn(유광) + Reflow
 4. HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBS, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

NO.	PART NAME	PART NO.	MATERIAL	FINISH	QTY.
①	060 8M SMD HOUSING	MG676325	SEE TABLE	SEE TABLE	1
②	060 SMD MALE TM'L (L)	ST792610-2	BRASS	Sn 무도금(무광)-Reflow	4
③	060 SMD MALE TM'L (S)	ST792611-2	BRASS	Sn 무도금(무광)-Reflow	4
④	060 SMD SIDE BRACKET	ST792612-2	BRASS	Sn 무도금(무광)	2

NO.	REVISION	DATE	BY	CHK	APP	DATE
DR	LUY	'14.12.31	CHK	YSW	'14.12.31	
CHK			APP	BIN	'14.12.31	

MATERIAL	FINISH	WIRE RANGE	INSULATION	CLASS	TYPE	PART NO.
SEE TABLE	SEE TABLE	SEE TABLE	SEE TABLE	SEE TABLE	1/1	MG6458B3

APPROVED
 2016-03-11
 KOREA ELECTRIC TERMINAL CO., LTD.
 KOREA ELECTRIC TERMINAL CO., LTD.
 ISSUE MARK