

CUSTOMER DRAWING REF. NO. MG645885

GENERAL TOLERANCE (TERMINAL)					GENERAL TOLERANCE (HOUSING)					USED ON	
10MAX	20MAX	45MAX	ANGLE	ECCENT	10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT
±0.2	±0.25	±0.3	±30°	0.1	±0.2	±0.3	±0.55	±0.95	±1.4	±30°	0.1

SECTION A-A

SECTION B-B

DETAIL C  
(S= 5/1)

NO.	MATERIAL	COLOR
0	NATURAL	
1	PPS-GF40	RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8		LIGHT GREEN
9		MAGENTA
11		ORANGE

P.C.B. LAYOUT  
(GENERAL TOLERANCE : ±0.1)

주 기

- 기능상 유해한 BURR 및 변형이 없도록.
- 적용 FEMALE HOUSING : MG655829
- 단차 주석 도금 - TYPE A Sn(무광), (MS915-01)  
Ni 이치 도금 + Sn(무광) + Reflow
- 재용내 함유분 6대 유해물질 (납,수은,카드뮴,크롬, PbB6,PBDE6)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

- MUST BE FREE OF BURR AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICATION FEMALE HOUSING : MG655829
- TIN-PLATED TERMINAL - TYPE A Sn(MATTE), (MS915-01)  
Ni-PLATED UNDER + Sn(MATTE) + Reflow
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBB6, PBDE6) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU EU ELV DIRECTIVE & RoHS REGULATION.

NO.	PART NAME	PART NO.	MATERIAL	FINISH	QTY.
①	060 18M SMD HOUSING	MG676327	SEE TABLE	SEE TABLE	1
②	060 SMD MALE TM'L (L)	ST792610-2	BRASS	Sn 후도금(무광)-Reflow	9
③	060 SMD MALE TM'L (S)	ST792611-2	BRASS	Sn 후도금(무광)-Reflow	9
④	060 SMD SIDE BRACKET	ST792612-2	BRASS	Sn 후도금(무광)	2

APPROVED  
2016-03-10  
KOREA ELECTRIC  
TERMINAL CO., LTD.  
Korea Electric Te  
rminol Co., Ltd.

ISSUE MARK

MATERIAL	SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE	
WIRE RANGE	CLASS	TYPE 060
INSULATION	TYPE	
SCALE	PART NO.	MG645885
DATE	PART NAME	060 18M SMD ASSY