






SECTION A-A



SECTION B-B

GENERAL TOLERANCE (HOUSING)							USED ON
10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	


NO.	PART NO.	PART NAME	COLOR	MATERIAL	REMARKS
1	MG671437	91A(030) 6F HS'G	NATURAL	PBT	
2	MG671438	91A(030) 6F R/ HOLDER	NATURAL	LYLON66	

주 기

- 지시하지 않은 R은 전부 0.5로 할것.
- 기능상 유해한 BURR 및 미성형이 없을것.
- 상대 HOUSING PART NO. : MG643358
- 적용 TERMINAL NO. : ST730913/ST730914

NOTE

- UNLESS OTHERWISE SPECIFIED ALL RADIUS TO BE 0.5 RADIUS.
- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE HOUSING NO. : MG643358
- APPLICABLE TERMINAL NO. : ST730913/ST730914



				MATERIAL	SEE TABLE		KOREA ELECTRIC TERMINAL CO., LTD.
				FINISH	SEE TABLE		CLASS
				WIRE RANGE	06.01.04	INSULATION	TYPE 7283-8660
				DR	03.02.14	SCALE	PART NO. MG651439
DR. BIN, '02.03.04	CHK			APP. DATE	03.02.14	SCALE	2/1
CHK	APP. <i>Chen</i>	3/2		PART NAME	91A(030) 6F HOUSING ASSY(A06FW)		