



GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG672980	040III 22P FEMALE HS'G	PBT	NATURAL
②	MG672981	040III 22P FEMALE R/HOLDER (A)	PBT	NATURAL
③	MG672982	040III 22P FEMALE R/HOLDER (B)	PBT	NATURAL

주 기

1. 기능상 유해한 BURR 및 미성형이 없을것.
2. 상대 HOUSING PART NO. : MG642979
3. 적용 TERM' : ST730770 / ST730960

NOTE

1. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE HOUSING : MG642979
3. APPLICABLE TERMINAL : ST730770 / ST730960



ISSUE MARK

MATERIAL	SEE TABLE	KET KOREA ELECTRIC TERMINAL CO., LTD.	
FINISH	SEE TABLE		
WIRE RANGE		CLASS 040III	
INSULATION		TYPE	
LTR	REVISION RECORD	DR	PART NO. MG652983
DR	KYM 2004.01.30	CHK	
CHK	01.30	APP.	
DATE	01.30	SCALE	2/1
PART NAME		040III 22P FEMALE ASS'Y	