



GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG672980	040III 22P FEMALE HS'G	PBT	NATURAL
②	MG672981	040III 22P FEMALE R/HOLDER (A)	PBT	NATURAL
③	MG672982	040III 22P FEMALE R/HOLDER (B)	PBT	NATURAL

주 기

- 기능상 유해한 FLASH, WELDLINE, 변형등이 없을 것.
- 상대 HOUSING PART NO. : MG642979
- 적용 TERM' : ST730770 / ST730960
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가 크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

- MUST BE FREE OF FLASH, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE HOUSING : MG642979
- APPLICABLE TERMINAL : ST730770 / ST730960
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

APPROVED

2018-12-11

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Te
rminal Co., LTD.

ISSUE MARK

						MATERIAL	SEE TABLE	KET KOREA ELECTRIC ENGINEERED TERMINAL CO., LTD.
						FINISH	SEE TABLE	
						WIRE RANGE		CLASS 040III
						INSULATION		TYPE
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE 2/1	PART NO. MG652983
	DR. KYM 2004.01.30		CHK.			PART NAME		040III 22P FEMALE ASS'Y
	CHK. KKJ 01.30		APP.		01.30			