CUSTOMER DRAWING

PART NO. MG652987

GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	





SEC A-A





주 기

1. 기능상 유해한 BURR 및 미성형이 없을것.
2. 상대 HOUSING PART NO. : MG642984
3. 적용 TERM' : ST730770 / ST730960

NOTE

1. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE HOUSING : MG642984
3. APPLICABLE TERMINAL : ST730770 / ST730960



NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG672988	04011I 2P FEMALE HS'G	PBT	NATURAL
②	MG672989	04011I 2P FEMALE R/HOLDER	PBT	NATURAL

한국단자공업주식회사 출 2004. 06.21 도 연구개발1팀

ISSUE MARK

LTR	REVISION RECORD	DR. CHK.	APP.	DATE
DR.	KYM 2004.01.30	CHK.		
CHK.	01.30	APP.		01.30

MATERIAL	SEE TABLE	KET (ENGINEERED)	KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE		
WIRE RANGE		CLASS	04011I
INSULATION		TYPE	
TOLERANCE EXCEPT AS NOTED	SEE TABLE	SCALE	2/1
PART NO.	MG652987		
PART NAME	04011I 2P FEMALE ASS'Y		

DIMENSIONS IN MM