



GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

**주 기**

- 기능상 유해한 BURR 및 미성형이 없을것.
- 상대 HOUSING PART NO. : MG642984
- 적용 TERM' : ST730770 / ST730960
- 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

**NOTE**

- MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE HOUSING : MG642984
- APPLICABLE TERMINAL : ST730770 / ST730960
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

NO.	MATERIAL	COLOR
* 0	PBT	NATURAL
1		RED
2		BLUE
3		YELLOW
40		DARK GRAY
41		LIGHT GRAY
△* 5		BLACK
6		DARK GREEN
△* 7		BROWN
8		LIGHT GREEN
9		MAGENTA
11	ORANGE	

NO.	PART NAME	PART NO.	MATERIAL	COLOR	QTY.
①	040III 2P FEMALE HS'G	MG672988	PBT	△ SEE TABLE	1
②	040III 2P FEMALE R/HOLDER	MG672989	PBT	NATURAL	1

**APPROVED**

2018-12-11

KOREA ELECTRIC  
TERMINAL CO., LTD.  
Korea Electric Te  
rminal Co., LTD.

ISSUE MARK

		MATERIAL		SEE TABLE		KOREA ELECTRIC
		FINISH		SEE TABLE		TERMINAL CO., LTD.
		WIRE RANGE			CLASS	040III
		INSULATION			TYPE	
△	ECO-1610-329 근거 도면 제작성 (HS'G BLACK, BROWN 누락 색상 표기)	LND	KMH	LSY	DATE	16.10.21
LTR	REVISION RECORD	DR.	CHK.	APP.	TOLERANCE EXCEPT AS NOTED	SCALE 2/1
DR.	KYM 2004.01.30	CHK.			PART NO.	MG652987
CHK.	KKJ 01.30	APP.			PART NAME	040III 2P FEMALE ASS'Y