



GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	

주 기

1. 기능상 유해한 BURR 및 미성형이 없을것.
2. 상대 HOUSING PART NO. : MG642996
3. 적용 TERM' : ST730770 / ST730960

NOTE

1. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE HOUSING : MG642996
3. APPLICABLE TERMINAL : ST730770 / ST730960

NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG673000	040III 4P FEMALE HS'G	PBT	NATURAL
②	MG673007	040III 4P FEMALE R/HOLDER (A)	PBT	NATURAL



ISSUE MARK

MATERIAL	SEE TABLE		KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE		
WIRE RANGE		CLASS	040III
INSULATION		TYPE	
LTR	REVISION RECORD	DR	
DR	KYM 2004.01.30	CHK	
CHK	2/2 01.30	APP	01.30
		SCALE	2/1
		PART NO.	MG652999
		PART NAME	040III 4P FEMALE ASS'Y