







GENERAL TOLERANCE (HOUSING)							USED ON
10 MAX	50 MAX	100 MAX	250 MAX	250 VR	ANGLE	ECCENT	
±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	



주 기

1. 기능상 유해한 BURR 및 미성형이 없을것.
2. 상대 HOUSING PART NO. : MG643002
3. 적용 TERM' : ST730770 / ST730960

NOTE

1. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE HOUSING : MG643002
3. APPLICABLE TERMINAL : ST730770 / ST730960



ISSUE MARK

NO.	PART NO.	PART NAME	MATERIAL	FINISH
①	MG673006	O40III 6P FEMALE HS'G	PBT	NATURAL
②	MG673007	O40III 6P FEMALE R/HOLDER (A)	PBT	NATURAL
③	MG673008	O40III 6P FEMALE R/HOLDER (B)	PBT	NATURAL

MATERIAL	SEE TABLE	KET KOREA ELECTRIC TERMINAL CO., LTD.		
FINISH	SEE TABLE			
WIRE RANGE		CLASS 040III		
INSULATION		TYPE		
LTR	REVISION RECORD	DR	SCALE 2/1	PART NO. MG653005
DR	KYM 2004.01.30	CHK		
CHK	01.30	APP.		PART NAME 040III 6P FEMALE ASS'Y