



GENERAL TOLERANCE (HOUSING)

| | | | | | | | | | |
|-------|-------|-------|-------|--------|--------|--------|-------|-------|---------|
| 10MAX | 30MAX | 50MAX | 70MAX | 100MAX | 120MAX | 250MAX | 250VR | ANGLE | USED ON |
| ±0.15 | ±0.20 | ±0.30 | ±0.40 | ±0.50 | ±0.75 | ±0.90 | ±1.40 | ±30' | |

| NO. | MATERIAL | COLOR |
|-----|-------------|------------|
| 0 | P B T | NATURAL |
| 1 | | RED |
| 2 | | BLUE |
| 20 | | JADE |
| 3 | | YELLOW |
| 4 | | GRAY |
| 40 | | DARK GRAY |
| 41 | | LIGHT GRAY |
| 5 | | BLACK |
| 6 | | DARK GREEN |
| 7 | | BROWN |
| 8 | LIGHT GREEN | |
| 9 | MAGENTA | |
| 11 | ORANGE | |

주 기

- 기능상 유해한 BURR 및 WELDLINE 등이 없을것.
- 적용 TERMINAL (025II) : ST731374-3, ST731375-3
- 상대 HOUSING : MG645877
- SPACER는 본 도면과 같이 1차 LOCK'G 상태로 유지, 공급할것.
- 제품내 함유된 6대 유해물질(납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

- MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
- APPLICABLE TERMINAL (025II) : ST731374-3, ST731375-3
- MATCHING HOUSING : MG645877
- THE MOLD DRAWING IN THE SAME WAY, SPACER IS NORMAL CONDITION MAINTENANCE AND SUPPLY WITH FIRST LOCKING.
- 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

| NO. | PART NAME | PART NO. | MATERIAL | COLOR | QTY. |
|-----|-------------------|------------|-----------|-----------|------|
| 1 | 025II 12F HOUSING | MG676305 | SEE TABLE | SEE TABLE | 1 |
| 2 | 025II 12F SPACER | MG676306-3 | PBT | YELLOW | 1 |

APPROVED

2021-10-20

KOREA ELECTRIC
TERMINAL CO., LTD.
Korea Electric Te
rminal Co., LTD.

ISSUE MARK

| NO. | REVISION | DATE | BY | CHECKED | DATE |
|---------------------|------------------------|-----------|--------------------|---------|------|
| 11 | ECO-2102-142 근거 도면 제작성 | '21.02.15 | SDI KSC CJH | | |
| 10 | ECO-2002-277 근거 도면 제작성 | '20.02.24 | SDI KSC CJH | | |
| 9 | ECO-1902-306 근거 도면 제작성 | '19.03.14 | LND KSC CJH | | |
| 8 | ECO-1803-396 근거 도면 제작성 | '18.03.27 | JH.K YSW SSH | | |
| 7 | ECO-1712-265 근거 도면 제작성 | '17.12.18 | JH NKT CJH | | |
| 6 | ECO-1703-170 근거 도면 제작성 | '17.03.14 | YTK CJH | | |
| LTR REVISION RECORD | | | DR. | CHK. | APP. |
| DR. SYC '14.10.10 | | | CHK. YSW '14.10.10 | | |
| CHK. | | | APP. BIN '14.10.10 | | |

| | | |
|---------------------------|----------------|------------|
| MATERIAL | SEE TABLE | |
| FINISH | SEE TABLE | |
| WIRE RANGE | | CLASS |
| INSULATION | | TYPE 025II |
| TOLERANCE EXCEPT AS NOTED | SEE TABLE | SCALE 2/1 |
| PART NAME | 025II 12F ASSY | |
| PART NO. | 9 MG655823 | |