



GENERAL TOLERANCE (HOUSING)										USED ON
10MAX	30MAX	50MAX	70MAX	100MAX	125MAX	250MAX	250VR	ANGLE	ECCENT	
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30'	0.1	

주 기

1. 기능상 유해한 BURR 및 WELDLINE 등이 없을것.
2. 적용 TERMINAL(O25II) : ST731374, 731375
3. 상대 HOUSING : MG645886
4. SPACER는 1차 LOCK 상태로 유지, 공급할 것.
5. 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, BPDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 지정한 최대 허용 농도를 초과해서는 안된다.

NO.	MATERIAL	COLOR
* 0	P B T	NATURAL
1		RED
2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
△* 5		BLACK
6		DARK GREEN
7		BROWN
8	LIGHT GREEN	
9	MAGENTA	
11	ORANGE	

NOTE

1. MUST BE FREE OF FLASH, SINK AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL(O25II) : ST731374, 731375
3. MATCHING HOUSING : MG645886
4. SPACER IS SUPPORT WITH THE 1st LOCK CONDITION.
5. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

APPROVED
2021-10-18
 KOREA ELECTRIC
 TERMINAL CO., LTD.
 Korea Electric Te
 rminial Co., LTD.

NO.	PART NAME	PART NO.	MATERIAL	COLOR	QTY.
1	O25II 20F HOUSING	MG676335	SEE TABLE	SEE TABLE	1
2	O25II 20F SPACER	MG676336	PBT	YELLOW	1

MATERIAL	SEE TABLE	KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE	
WIRE RANGE		CLASS
INSULATION		TYPE O25II
LTR	REVISION RECORD	PART NO. MG655830
DR.	KSY '14.12.30	SCALE 2/1
CHK.	YSW '14.12.31	PART NAME O25II 20F ASSY
APP.	BIN '14.12.31	

ISSUE MARK