



GENERAL TOLERANCE (HOUSING)

10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	USED ON
±0.15	±0.20	±0.30	±0.40	±0.50	±0.75	±0.90	±1.40	±30'	

주 기

1. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것,
2. 적용 TERMINAL ; ST731374, ST731375
3. 상대물 HOUSING; MG646090
4. 제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다,

NOTE

1. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION,
2. APPLICABLE TERMINAL ; ST731374, ST731375
3. APPLICABLE FEMALE HOUSING ; MG646090
4. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

**APPROVED**

2019-11-06

KOREA ELECTRIC  
TERMINAL CO., LTD.

Korea Electric Te  
rminl Co., LTD.

NO.	MATERIAL	COLOR
* 0	PBT	NATURAL
1		RED
△* 2		BLUE
20		JADE
3		YELLOW
4		GRAY
40		DARK GRAY
41		LIGHT GRAY
5		BLACK
6		DARK GREEN
7		BROWN
8	LIGHT GREEN	
9	MAGENTA	
11	ORANGE	

ISSUE MARK

NO.	PART NAME	PART NO.	MATERIAL	COLOR	Q'TY
1	02511 4F HOUSING	MG676874	SEE TABLE	SEE TABLE	1
2	02511 4F SPACER	MG676875-3	PBT	YELLOW	1

MATERIAL	SEE TABLE	<b>KET</b> ENGINEERED	KOREA ELECTRIC TERMINAL CO., LTD.
FINISH	SEE TABLE		
WIRE RANGE		CLASS	025
INSULATION		TYPE	비방수
ECO-1909-241 근거 도면 제작상	KSC	CJH	19.09.26
LTR	REVISION RECORD	DR.	CHK.
DR.	JDR 2017.01.19	CHK.	
CHK.	SSH 2017.01.23	APP.	BIN 2017.01.23
TOLERANCE EXCEPT AS NOTED	SEE TABLE	SCALE	2/1
PART_NAME	02511 4F ASSY		