



GENERAL TOLERANCE (HOUSING)

10 MAX	30 MAX	50 MAX	70 MAX	100 MAX	120 MAX	250 MAX	250 VR	ANGLE	ECCENT	USED ON
±0.15	±0.2	±0.3	±0.4	±0.5	±0.75	±0.9	±1.4	±30'	0.1	

주 기

1. 기능상 유해한 BURR 및 WELDLINE 등이 없을 것.
2. 적용 TERMINAL : ST731274-3, ST731275-3
적용 DUMMY SEAL : MG683898
3. 제품내 함유된 6대 유해물질 (납, 수은, 카드뮴, 6가크롬, PBBs, PBDEs)은 EU ELV 지침 및 RoHS 법규에서 지정한 최대 허용 농도를 초과해서는 안된다.

NOTE

1. MUST BE FREE OF BURR, WELDLINE AND IMPERFECTION THAT AFFECT FUNCTION.
2. APPLICABLE TERMINAL : ST731274-3, ST731275-3
APPLICABLE DUMMY SEAL : MG683898
3. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD, MERCURY, CADMIUM, HEXAVALENT CHROMIUM, PBBs, PBDEs) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE & RoHS REGULATION.

NO.	MATERIAL	COLOR
0	SEE TABLE	NATURAL
1		RED
11		ORANGE
2		BLUE
22		JADE
3		YELLOW
4		GRAY
41		LIGHT GRAY
42		DARK GRAY
* 5	BLACK	
61	LIGHT GREEN	
62	DARK GREEN	
7	BROWN	
9	MAGENTA	

SECTION A-A

ASSY NO.	ASSY NAME
MG657045	060 WP 3F ASSY (0.8T / NON CPA TYPE)
MG657015	060 WP 3F ASSY (0.8T)

NO	PART NO.	PART NAME	MATERIAL	FINISH	Q'TY	Q'TY
1	MG677169	060 WP 3F HOUSING (0.8T)	PBT GF15%	BLACK	1	1
2	MG677172	060 WP 3F FRONT HOLDER (0.8T)	PBT	NATURAL	1	1
3	R603647	060 WP 3F INNER SEAL (0.8T)	SILICONE	RED	1	1
4	MG676008-1N	375 WP 2F CPA	PA66	RED	1	-

ECO-2110-183 근거 도면 제작성 (도면 시 용법 참조)	STJ	KSC	HYJ	21.10.20	MATERIAL	SEE TABLE	 KOREA ELECTRIC TERMINAL CO., LTD.						
ECO-2108-136 근거 도면 제작성 (PIN MAP 식별)	YDH	-	HYJ	21.8.12	FINISH	SEE TABLE							
ECO-1912-163 근거 도면 제작성 (PIN MAP 식별)	JMS	AJH	CMS	19.12.12	WIRE RANGE	-	CLASS	060 (0.8T)					
도면 이관 (개별 -> 일반) ECO-1909-296 근거 도면 제작성	JMS	AJH	CMS	19.10.01	INSULATION	-	TYPE	WP					
LTR	REVISION RECORD				DR.	CHK.	APP.	DATE	TOLERANCE EXCEPT AS NOTED	SCALE	2/1	PART NO.	SEE TABLE
DR.	AJH 18.05.14			CHK.					PART_NAME	060 WP 3F ASSY (0.8T)			
CHK.				APP.	CMS 18.05.14								

APPROVED

2021-10-21

KOREA ELECTRIC TERMINAL CO., LTD.
Korea Electric Terminal Co., LTD.

ISSUE MARK