



ISO VIEW

USED ON

10MAX	50MAX	100MAX	250MAX	250VR	ANGLE	ECCENT
±0.2	±0.3	±0.55	±0.95	±1.4	±30°	0.1

1. MUST BE FREE OF BURR, WELDLINE

AND IMPERFECTION (HA) AFFECT FUNCTION.

2. APPLICABLE TERMINAL : ST730948-3, ST730993-3

3. APPLICABLE HOUSING : MG615163

4. 6 HAZARDOUS SUBSTANCES IN PARTS (LEAD,MERCURY, CADMIUM,HEXAVALENT CHROMIUM,PBBS,PBDES) SHALL NOT EXCEED THE MAXIMUM PERMISSIBLE

CONCENTRATION PRESCRIBED UNDER EU ELV DIRECTIVE

& ROHS REGULATION.

1. 기능상 유해한 BURR 및 WELDLINE등이 없을것.
- 2.작용 TERMINAL: ST730948-3, ST730993-3
- 3.작용 HOUSING : MG615163
- 4.제품내 함유된 6대 유해물질 (납,수은,카드뮴,6가크롬, PBBs,PBDEs)은 EU TiV 지침 및 RoHS 법규에서 지정된 최대 허용 농도를 초과해서는 안된다.

						MATERIAL	PAGE(V0)	KET KOREA ELECTRIC TERMINAL CO., LTD.
						FINISH	RED	
						WIRE RANGE	CLASS	
							250	
						INSULATION	TYPE	
LTR	REVISION RECORD	DR.	CHK.	APP.	DATE	INDICATE AS ABOVE	SCALE	PART NO.
DR.	CJH '10.01.11						SEE TABLE	2/1
CHK.							PART NAME	
							250 7F R/HOLDER	